

**Technical Data Sheet**  
**Microphone Cables**  
**“Ultra Flex”**



2833 West Chestnut Street  
 Washington, PA 15301  
 Toll Free: (800) 245-4964  
 Fax: (724) 222-6420  
 www.westpenn-wpw.com

<b>PART NUMBER:</b>	<b>534</b>
<b>DESCRIPTION:</b>	22/4 Ultra flexible stranded bare copper conductors, shielded with a flexible thermoplastic elastomer jacket that is oil resistant.
<b>NEC RATING:</b>	CM, NEC Article 800
<b>APPROVALS:</b>	(UL) or (ETL)us Listed
<b>APPLICATION:</b>	Indoor for: Pro Audio, Sound Systems, Recording Studio, Post Production facilities.

**Construction Parameters:**

Conductor	22 AWG Tinned Copper
Stranding	65x40
Insulation Material	Polyethylene
Insulation Thickness	0.010" Nom.
Number of Conductors	4
Shield	95% Tinned Copper Braid (8.5 ohms)
Drain	--
Jacket Material	PVC
Jacket Thickness	0.010" Nom.
Overall Cable Diameter	.237" Nom.
Approximate Cable Weight	45 Lbs/1M' Nom.
Flame Rating	UL 1685

**Electrical & Environmental Properties:**

Temperature Rating	-20deg C to 60deg C
Operating Voltage	300 V RMS
Max. Capacitance Between Conductors @ 1 KHz	42 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	45 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	17 Ohms/1M' Nom.
Insulation Colors	2 Blue, 2 White
Jacket Color	Gray, Blue, Orange, Red, Yellow, Black
RoHS Compliant	--

**Mechanical Properties:**

Max. Recommended Pull Tension	70 lbs.
Min. Bend Radius (Install)	2.3"

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Standard Lengths are 1000ft. The Jacket is sequentially footmarked. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.