

Technical Data Sheet
AES/EBU Digital
Plenum Audio Cables



2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com

PART NUMBER:	DA252402
DESCRIPTION:	2 Pair 24 Awg. Stranded tinned copper conductors, individually shielded with an overall jacket.
NEC RATING:	CMP, NEC Article 800
APPROVALS:	(UL) Listed
APPLICATION:	Indoor Plenum for: Pro Audio, Sound Systems, Recording Studio, Post Production facilities.

Construction Parameters:

Conductor	24 AWG Tinned Copper
Stranding	7x32
Insulation Material	Low-Loss Foam
Insulation Thickness	0.020" Nom.
Number of Conductors	4 (2 Pair)
Shield	100% Aluminum Polyester Foil
Drain	Stranded Tinned Copper
Jacket Material	PVDF
Jacket Thickness	0.010" Nom.
Overall Cable Diameter	.238" Nom.
Approximate Cable Weight	25 Lbs/1M' Nom.
Flame Rating	NFPA 262 Flame Test

Electrical & Environmental Properties:

Temperature Rating	-10deg C to 60deg C
Operating Voltage	300 V RMS
Max. Capacitance Between Conductors @ 1 KHz	12.5 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	22.5 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	26 Ohms/1M' Nom.
Velocity of Propagation	78% Nom.
Impedance	110Ω
Insulation Colors	1. Black/Red, 2 Black/White
Jacket Color	Gray
RoHS Compliant	--

Mechanical Properties:

Max. Recommended Pull Tension	45 lbs.
Min. Bend Radius (Install)	2.3"

Specification Issue Date: 7/06

This document is the property of West Penn Wire.
The information contained herein is considered
Proprietary and not to be reproduced by any means
Without written consent of West Penn Wire

Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our
knowledge, is true and accurate. However, since
conditions of use are beyond our control, all
recommendations or suggestions are presented
without guarantee or responsibility on our part. We
disclaim all liability in connection with the use of
information contained herein or otherwise.