

Technical Data Sheet

Fire Alarm Cables

WEST PENN WIRE



2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com

| | |
|---------------------|--|
| PART NUMBER: | 60990B |
| DESCRIPTION: | 16/2 Solid bare copper conductors, shielded with an overall jacket. |
| NEC RATING: | FPLP, NEC Article 760 |
| APPROVALS: | (UL) or (ETL)us Listed |
| APPLICATION: | Indoor within ducts, plenums, and other spaces used for environmental air for (Audio Circuits, Control Circuits, Initiating Circuits, Notification Circuits) |

Construction Parameters:

| | |
|--------------------------|------------------------------|
| Conductor | 16 AWG Bare Copper |
| Stranding | Solid |
| Insulation Material | Polymer Alloy |
| Insulation Thickness | 0.010" Nom. |
| Number of Conductors | 2 |
| Shield | 100% Aluminum Polyester Foil |
| Drain | Stranded Tinned Copper |
| Jacket Material | Flexible Plenum |
| Jacket Thickness | 0.015" Nom. |
| Overall Cable Diameter | 0.166" Nom. |
| Approximate Cable Weight | 29 Lbs/1M' Nom. |
| Flame Rating | NFPA- 262 Flame Test |

Electrical & Environmental Properties:

| | |
|--|---------------------|
| Temperature Rating | -10deg C to 60deg C |
| Operating Voltage | 300 V RMS |
| Max.Capacitance Between Conductors @ 1 KHz | 61 pf/ft Nom. |
| Capacitance Between Conductors to Shield @ 1 KHz | 110 pf/ft Nom. |
| DC Resistance per Conductor @ 20deg C | 4.1 Ohms/1M' Nom. |
| Insulation Colors | Black, Red |
| Jacket Color | Red |
| RoHS Compliant | Yes |

Mechanical Properties:

| | |
|-------------------------------|-----------|
| Max. Recommended Pull Tension | 76.4 lbs. |
| Min. Bend Radius (Install) | 1.75" |

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Cold Environment Precautions: Due to the nature of PVC Compounds to become non-pliable when stored or handled in ambient temperatures of 32 deg. F or less, we recommend the following:

“Prior to installation, condition the cable for at least 24 hours at room temperature to provide the best flex properties for ease of installation.”

Standard Lengths are 1000ft.

The Jacket is sequentially footmarked.

The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.