

Technical Data Sheet

Fire Alarm Cables



2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com

PART NUMBER:	961
DESCRIPTION:	16/1 Solid bare copper conductors
NEC RATING:	FPL, NEC Article 760
APPROVALS:	(UL) or (ETL)us Listed
APPLICATION:	Indoor for: Power –Limited Fire Protective Circuits

Construction Parameters:

Conductor	16 AWG Bare Copper
Stranding	Solid
Insulation Material	PVC
Insulation Thickness	0.020" Nom.
Number of Conductors	1
Shield	None
Drain	None
Overall Cable Diameter	0.091" Nom.
Approximate Cable Weight	12 Lbs/1M' Nom.
Flame Rating	NFPA- 262 Flame Test

Electrical & Environmental Properties:

Temperature Rating	-10deg C to 60deg C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	-- pf/ft Nom.
DC Resistance per Conductor @ 20deg C	4.1 Ohms/1M' Nom.
Insulation Colors	Black, Green, Brown, White, Red, Orange, Yellow
Jacket Color	
RoHS Compliant	

Mechanical Properties:

Max. Recommended Pull Tension	30 lbs.
Min. Bend Radius (Install)	1.0'

Specification Issue Date: 7/06

This document is the property of West Penn Wire.
The information contained herein is considered
Proprietary and not to be reproduced by any means
Without written consent of West Penn Wire

Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our
knowledge, is true and accurate. However, since
conditions of use are beyond our control, all
recommendations or suggestions are presented
without guarantee or responsibility on our part. We
disclaim all liability in connection with the use of
information contained herein or otherwise.