

# Technical Data Sheet

## Broadcast Audio Cables



2833 West Chestnut Street  
Washington, PA 15301  
Toll Free: (800) 245-4964  
Fax: (724) 222-6420  
www.westpenn-wpw.com



---

<b>PART NUMBER:</b>	<b>77294</b>
<b>DESCRIPTION:</b>	16/2 Stranded tinned copper conductors, shielded with an overall jacket.
<b>NEC RATING:</b>	CM, NEC Article 800, CL2, NEC Article 725
<b>APPROVALS:</b>	(UL) or (ETL)us Listed
<b>APPLICATION:</b>	Indoor for: Pro Audio, Sound Systems, Recording Studio, Production Facilities.

---

### Construction Parameters:

Conductor	16 AWG Tinned Copper
Stranding	19x29
Insulation Material	Polyethylene
Insulation Thickness	0.032" Nom.
Number of Conductors	2 (1 Pair)
Shield	100% Aluminum Polyester Foil
Drain	Stranded Tinned Copper
Jacket Material	PVC
Jacket Thickness	0.032" Nom.
Overall Cable Diameter	0.310" Nom.
Approximate Cable Weight	47 Lbs/1M' Nom.
Flame Rating	UL 1685

---

### Electrical & Environmental Properties:

Temperature Rating	-20deg C to 60deg C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	23 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	44 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	4.2 Ohms/1M' Nom.
Insulation Colors	Black, Clear
Jacket Color	Gray
RoHS Compliant	--

---

### Mechanical Properties:

Max. Recommended Pull Tension	69 lbs.
Min. Bend Radius (Install)	3.1"

---

Specification Issue Date: 7/06

This document is the property of West Penn Wire.  
The information contained herein is considered  
Proprietary and not to be reproduced by any means  
Without written consent of West Penn Wire

Standard Lengths are 1000ft.  
The Jacket is sequentially footmarked.  
The information presented here is, to the best of our  
knowledge, is true and accurate. However, since  
conditions of use are beyond our control, all  
recommendations or suggestions are presented  
without guarantee or responsibility on our part. We  
disclaim all liability in connection with the use of  
information contained herein or otherwise.