

Technical Data Sheet
RG58 Coaxial 50 Ohm



2833 West Chestnut Street
 Washington, PA 15301
 Toll Free: (800) 245-4964
 Fax: (724) 222-6420
 www.westpenn-wpw.com

PART NUMBER:	813
DESCRIPTION:	RG58/U – 1 Conductor 20AWG Solid, 95% Tinned copper braid and an overall PVC Jacket.
NEC RATING:	CM
APPROVALS:	(UL) C(UL) Listed or c(ETL)us Listed
APPLICATION:	Indoor for: 50 Systems

Construction Parameters:

Conductor	20 AWG Tinned Copper
Stranding	Solid
Insulation Material	Gas Injected Polyethylene
Insulation Thickness	.116" Nom.
Number of Conductors	1 Center Conductor
Shield	95% Tinned Copper Braid
Jacket Material	PVC
Overall Cable Diameter	0.194" Nom.
Approximate Cable Weight	18 Lbs/1M' Nom.
Flame Rating	UL 1685

Electrical & Environmental Properties:

		<u>Mhz</u>	<u>db/100ft</u>
Temperature Rating	-20deg C to 60deg C	1	.35
Max.Capacitance Between Conductors @ 1 KHz	25 pf/ft Nom.	10	1.4
Velocity of Propagation	78% Nom.	50	3.5
Impedance	50 ohms Nom.	100	4.8
DC Resistance per Conductor @ 20deg C	10.1 Ohms/1M' Nom.	400	9.5
Jacket Color	Black	500	10.4
RoHS Compliant	--	900	14.5

Mechanical Properties:

Max. Recommended Pull Tension	41 lbs.
Min. Bend Radius (Install)	2.0"

Connectors and Accessories

50 Ohm 3 pc. BNC CN-BM53-13

Specification Issue Date: 3/10

This document is the property of West Penn Wire.
 The information contained herein is considered
 Proprietary and not to be reproduced by any means
 Without written consent of West Penn Wire

Standard Lengths are 1000ft.
 The Jacket is sequentially footmarked.
 The information presented here is, to the best of our
 knowledge, is true and accurate. However, since
 conditions of use are beyond our control, all
 recommendations or suggestions are presented
 without guarantee or responsibility on our part. We
 disclaim all liability in connection with the use of
 information contained herein or otherwise.