

Technical Data Sheet

RG6/U Type CATV Coaxial Cable



2833 West Chestnut Street
 Washington, PA 15301
 Toll Free: (800) 245-4964
 Fax: (724) 222-6420
 www.westpenn-wpw.com

PART NUMBER:	6140
DESCRIPTION:	RG6/U – 1 Conductor 18 AWG Solid, 100% Al. Foil + 61% Al. Braid, Flooding material and an overall PE Jacket.
NEC RATING:	-- Outdoor Flooded
APPROVALS:	--
APPLICATION:	Outdoor: CATV/MATV

Construction Parameters:

Conductor	18 AWG Copper Covered Steel
Stranding	Solid
Insulation Material	Gas Injected Polyethylene
Insulation Thickness	.180" Nom.
Number of Conductors	1 Center Conductor
Shield	100% Al Foil + 61% Al. Braid
Flooding Material	Yes
Jacket Material	Sunlight Resistant PE - Polyethylene
Overall Cable Diameter	0.275" Nom.
Approximate Cable Weight	35 Lbs/1M' Nom.
Flame Rating	--

Electrical & Environmental Properties:

		<u>Mhz</u>	<u>db/100ft</u>
Temperature Rating	-20deg C to 60deg C	5	.54
Max.Capacitance Between Conductors @ 1 KHz	16.2 pf/ft Nom.	55	1.55
Velocity of Propagation	82% Nom.	100	1.90
Impedance	75 ohms Nom.	270	3.07
DC Resistance per Conductor @ 20deg C	28 Ohms/1M' Nom.	400	3.85
Jacket Color	Black	550	4.62
RoHS Compliant	--	750	5.40
		1000	6.3
		1800	8.85
		2250	9.99
		3000	11.9

Mechanical Properties:

Max. Recommended Pull Tension	126 lbs.
Min. Bend Radius (Install)	2.5"

Connectors and Accessories

F Crimp:	CN-56AQ
F Compression:	CN-CSF-6 OR CN-FCP-6

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Standard Lengths are 1000ft.
 The Jacket is sequentially footmarked.
 The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

