

Technical Data Sheet

RG6/U Type CCTV Coaxial Cable



2833 West Chestnut Street
 Washington, PA 15301
 Toll Free: (800) 245-4964
 Fax: (724) 222-6420
 www.westpenn-wpw.com

PART NUMBER:	806
DESCRIPTION:	RG6/U – 1 Conductor 18 AWG Solid, 95% Bare copper braid and an overall PVC Jacket.
NEC RATING:	CMR
APPROVALS:	(UL) C(UL) Listed or c(ETL)us Listed
APPLICATION:	Indoor for: Security Cable - CCTV

Construction Parameters:

Conductor	18 AWG Bare Copper
Stranding	Solid
Insulation Material	Gas Injected Polyethylene
Insulation Thickness	.180" Nom.
Number of Conductors	1 Center Conductor
Shield	95% Bare Copper Braid
Jacket Material	PVC
Overall Cable Diameter	0.270" Nom.
Approximate Cable Weight	26 Lbs/1M' Nom.
Flame Rating	UL 1666

Electrical & Environmental Properties:

		<u>Mhz</u>	<u>db/100ft</u>
Temperature Rating	-20deg C to 60deg C	1	.24
Max.Capacitance Between Conductors @ 1 KHz	16.2 pf/ft Nom.	10	.52
Velocity of Propagation	82% Nom.	50	1.18
Impedance	75 ohms Nom.	100	1.83
DC Resistance per Conductor @ 20deg C	6.5 Ohms/1M' Nom.	400	3.95
Jacket Color	Black	700	5.38
RoHS Compliant	Yes	1000	6.45

Mechanical Properties:

Max. Recommended Pull Tension	41 lbs.
Min. Bend Radius (Install)	2.5"

Connectors and Accessories

75 ohm BNC Crimp	CN-BM73-5	Crimp Tool: TL-107	Strip Tool: TL-121
Compression BNC 75 ohm	CN-CSBNC-6	Comp. Tool: TL-SNSA	Strip Tool: TL-CSST
Compression RCA	CN-CSRCA-6	Comp. Tool: TL-SNSA	Strip Tool: TL-CSST

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Standard Lengths are 1000ft.
 The Jacket is sequentially footmarked.
 The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

