



2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com

Technical Data Sheet Access Control Flexible Plenum Lickity Split Design

PART NUMBER:	LS251822
DESCRIPTION:	Access Control Composite Cable: Card Reader Cable, REX Cable, Lock Power Cable, Door Contact Cable. Lickity Split Design
NEC RATING:	CMP
APPROVALS:	(UL) C(UL) Listed
APPLICATION:	Indoor within ducts, plenums and other spaces used for environmental air for: (Access Control)

Construction Parameters: Card Reader

Conductor	22 AWG Bare Copper
Stranding	7x30
Insulation Material	Polymer Alloy Thermoplastic
Insulation Thickness	PVC: 0.010" Nom.
Number of Conductors	6
Shield	Overall Shield
Drain	Yes
Jacket Material	Plenum PVC
Jacket Thickness	.015"
Overall Cable Diameter	0.182" Nom.
Jacket Color	Orange

Electrical Parameters: Card Reader

Nom. D.C.R.	17 ohms/1000ft
Nom. Capacitance pf/ft.	55pf/ft*, 99pf/ft**
	<ul style="list-style-type: none">• Capacitance between conductors• Capacitance between one conductor and the other to the shield

Construction Parameters: Door Contact

Conductor	22 AWG Bare Copper
Stranding	7x30
Insulation Material	Polymer Alloy Thermoplastic
Insulation Thickness	PVC: 0.010" Nom.
Number of Conductors	2
Shield	None
Drain	None
Jacket Material	Plenum PVC
Jacket Thickness	.015"
Overall Cable Diameter	0.110" Nom.
Jacket Color	White

Electrical Parameters: Door Contact

Nom. D.C.R.	17 ohms/1000ft
-------------	----------------

Construction Parameters: Request to Exit

Conductor	22 AWG Bare Copper
Stranding	7x30
Insulation Material	Polymer Alloy Thermoplastic
Insulation Thickness	PVC: 0.010" Nom.
Number of Conductors	4
Shield	None
Drain	None
Jacket Material	Plenum PVC
Jacket Thickness	.015"
Overall Cable Diameter	0.148" Nom.
Jacket Color	Blue

Electrical Parameters: Request to Exit

Nom. D.C.R.	17 ohms/1000ft
-------------	----------------

Construction Parameters: Lock Power

Conductor	18 AWG Bare Copper
Stranding	7x26
Insulation Material	Polymer Alloy Thermoplastic
Insulation Thickness	PVC: 0.010" Nom.
Number of Conductors	4
Shield	None
Drain	None
Jacket Material	Plenum PVC
Jacket Thickness	.015"
Overall Cable Diameter	0.189" Nom.
Jacket Color	Gray

Electrical Parameters: Lock Power

Nom. D.C.R.	6.2 ohms/1000ft
-------------	-----------------

Overall Cable Assembly:

Overall Cable Diameter	.425"
All conductor Colors	Black, Red, White, Green, Brown, Blue
Jacket Color	Lickity Split Design
RoHS Compliant	Yes

Specification Issue Date: 2/09

This document is the property of West Penn Wire.
The information contained herein is considered
Proprietary and not to be reproduced by any means
Without written consent of West Penn Wire

Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our
knowledge, is true and accurate. However, since
conditions of use are beyond our control, all
recommendations or suggestions are presented
without guarantee or responsibility on our part. We
disclaim all liability in connection with the use of
information contained herein or otherwise.